



Technical sheet Euroniche HB



Euroniche HB

Our HB Euro Niches for walls, made from Backer Board, available in sizes 30x30 cm, 30x60 cm, and 30x90 cm, offer a practical and aesthetic solution to optimize space in bathrooms, kitchens, or any area with ceramic cladding.

Manufactured with Backer Board, these niches guarantee high resistance, waterproofing, and durability. In addition, we offer the option to purchase our additional ESTB Euro Shelf, which can be placed according to the customer's needs.

Ideal for bathrooms, kitchens, and modern spaces where functionality and design meet.

The HB Euro Niche provides additional space to store everyday items while maintaining a clean and organized aesthetic. With our HB Euro Niches made from Backer Board, transform any wall into a functional and stylish element, ensuring a strong and durable installation using cutting-edge materials.







GENERAL CHARACTERISTICS

Length

Height

Available widths

Packaging

u./caja



FICHA TÉCNICA • TECNICAL DATASHEET

Technical sheet Euroniche HB

EURONICHE HB Height Length COLOURS

MATERIAL CHARACTERISTICS



INSTALLATION

Installation of the HB Euro Niche:

To ensure proper and long-lasting installation, follow these steps and recommendations. The surface must be clean, level, and prepared to receive the niche.

1 - Preparing the surface or wall:

Before installing the niche, make sure the wall is fully constructed. Create an opening at the desired location, respecting the dimensions of the selected niche.

2 - Fixing the niche:

Insert the HB Euro Niche into the opening and firmly attach it to the surface using appropriate adhesive or mechanical anchors, as required. Ensure it is level and aligned with the wall.

3 - Waterproofing:

In humid or wet areas such as bathrooms, use *Eurowaterproof.5* to waterproof the entire surface. This ensures optimal protection against moisture and guarantees the durability of the cladding, preventing leaks that could damage other areas of the building.

4 - Ceramic cladding:

Once waterproofed, proceed to apply the ceramic cladding directly onto the niche using an adhesive compatible with the chosen ceramic. Be sure to respect joints and finishes to achieve an aesthetic and functional result.

Additional recommendations:

- If an additional shelf is included, adjust its placement before applying the cladding.
- Protect the niche during work to prevent damage or unintentional displacement.
- Comply with current regulations and the instructions of the manufacturers of the products used.

By following these guidelines, you will achieve a professional, durable, and visually flawless installation. Euroshrink shall not be held liable for any damage resulting from misuse or improper storage.





FICHA TÉCNICA • TECNICAL DATASHEET

Technical sheet **Euroniche HB**

used, always avoiding products that could damage the finish.

For cleaning, it is advisable to use water and mild soap or detergent whenever possible to avoid stains. INFORMATION if chemical help is needed, do not use abrasives, strippers, or acids such as hydrochloric or perchloric acid,

Strong hapes like nausticks do not use abrasives, strippers, or acids such as hydrochioric or perchioric acids ac

- EUROSHRINK S.A. guarantees that the HB EURO NICHE complies with the specifications and quality the results of defects that may occur when using these techniques will always depend on the level of standards as described in our technical data sheet of the sales invoice.
 - For the warranty to be fully valid, proper installation, storage, and handling of the product after sale are required.